

PERFORMANCE DECLARATION

No. 3/2023 of 19.05.2023



Product type unique identification code: **Mass no. 5 (white clay-based) – Clinker cladding tile**

1. **Colours:** Ice power (22), Grey eminence (23), Black stone (26), Vanilla sky (27), Pacific pearl (28), Just white (29), Caramel street (30), Cafe latte (31), Glacier cave (HF43), Arctic storm (HF44), Aztec ghost (HF45), Silver rose (HF46), Platinum skies (HF47), Astro house (HF48), Grey satin (HF49), Pearl satin (HF53), Roman theatre (HF54), Rusty moon (HF56), Kings valley (HF58), Summerian city (HF59), Desert land (HF60), Sand pepper (HF61), Iron rock (HF62), Rusty stone (HF63), White night (HF64), Night sound (HF65), Basalt river (HF66), Earth skin (HF67), Calm umber (HF68), Dance umber (HF69), Meteor veneer (HF70), Snow brick (HF71), Silver fox (HF72), Vestero's walls (HF73), Winter field (HF74), Steel rebel (HF81), Volcanic wall (HF82).
Applicable to all formats on our offer.

2. Intended use(s):
For wall tiling (as finishing) in interiors and/or exteriors of building structures

3. Manufacturer:
**King Klinker S.A.
26 – 400 Przysucha
Skrzyńsko ul. Przemysłowa 56**

4. Authorised representative: **Not applicable**

5. Assessment and Verification of Constancy of Performance (AVCP) system(s) : **System 4**

6a. Harmonised standard:
EN 14411:2012 „Ceramic tiles – Definition, classification, characteristics, assessment and verification of constancy of performance and marking” Annex C, Natural

6b. Technical assessment body: **Not applicable**
Notified body (-ies): **Not applicable**

Declared performance

	General characteristics	Performance properties	Harmonized technical specification
7.	Reaction to fire	class A1	EN 14411:2012
	Water absorption	below 6%	
	Thermal shock resistance	Yes	
	External use durability	Yes	
	External use durability: resistance to frosting - defrosting	Yes	
	Dimension		
	- Length and width	±2.0% to maximum ±4mm	
- Thickness	±10%		
- Squareness	±1.0%		
- Surface flatness	±1.5%		
- Curvature of sides	±1.0%		

7.	Surface quality	Minimum 95% tiles should not have visible defects causing deterioration of the appearance of considerable surface of tiles.	EN 14411:2012
	Bonding strength / adhesion - cement adhesives - dispersion adhesives - reactive resin adhesive - masonry mortar	NPD NPD NPD NPD	

8. Relevant technical documentation or special technical documentation: **Not applicable**

Performance of the above specified product is in conformity with a set of performances declared. This performance declaration is issued in accordance with the Regulation (EU) no. 305/2011 at the exclusive liability of the above mentioned manufacturer.

Skrzyńsko 19.05.2023

.....
Place and date of issue

Signed on behalf of the manufacturer by :

Sylwester Czubak

Head of Quality Control Department

KIEROWNIK
Dziedzielnicy Kontroli Jakości

Sylwester Czubak
legible signature

(signature)