






| Product name | | Production location | |
|--|--------------------|--|--|
| Novara Antica (Without Chamfered Edge, without spacers) | NPD | Kessel | |
| Format | | | |
| Moulding method | | Wirecut | |
| DF60: 204 x 67 x 60 mm | | Between batches the average size and color may slightly differ. | |
| Essential Characteristics - EN1344 | | | |
| <div>CE</div> <div>NPD</div> | | <div>UKCA</div> <div>NPD</div> | |
| Reaction to fire | A1 | | |
| External fire performance | NPD | | |
| Dangerous substances | NL-BSB | | |
| Transverse breaking load | NPD | Category | |
| Unpolished slip/skid resistance USRV | NPD | Category | |
| Thermal conductivity | NPD | | |
| Durability against freeze thaw | NPD | Category | |
| Sustainable slip/skid resistance (PSRV) | NPD | Category | |
| Other Characteristics - EN1344 & BRL 2360 | | | |
| Paver quality 1 | NPD | Category | |
| Paver quality 1 Tolerances | <= 0,4 √dimensions | | |
| Paver quality 1 Range | R1 | Category | |
| Water absorption | <= 5% m/md | | |
| Abrasion resistance | NPD | Category | |
| Acid resistance | NPD | Category | |
| Other Characteristics - PTV 910 | | | |
| Standardized Quality Classes - PTV 910 | NPD | | |
| Water absorption - PTV 910 | W2 (<=5%,<=6%) | | |
| <div><div></div><div></div><div></div><div></div><div></div></div> | | | |
| Storage & handling | | Cutting | |
| <div>- Stock pavers on a clean surface and cover them</div> <div>- Blend from different pavers (pack) at the same time</div> <div>- Do not clean fresh masonry with hydrochloric acid</div> | | Dry Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3). | |